

---

---

# Product Information

A PRODUCT OF VALVOLINE, A DIVISION OF ASHLAND INC. USA



---

---

## VALVOLINE ALL FLEET TURBO 15W40

**Valvoline All Fleet Turbo 15W40** is formulated to provide optimum performance in modern naturally aspirated and turbo charged diesel engines operating under a wide variety of service conditions. It is blended with premium base stocks and high quality additive chemistry.

**Valvoline All Fleet Turbo 15W40** is recommended for all equipment such as trucks, buses, excavators, tippers & dozers fitted with turbo charged diesel engines.

Also suitable for other vehicles such as LCV's / MUV's of all makes.

## VALVOLINE ALL FLEET TURBO 15W40 ADVANTAGE

- High temperature piston deposit control
- Soot dispersancy and oil-thickening control
- Low temperature sludge protection
- Superior TBN retention to neutralize corrosive acids from combustion.
- Foam protection
- Oxidation inhibition
- Corrosion and rust inhibition
- Valve train wear protection

---

---

### **Performance levels / Approvals**

API CF-4/SG

---

---

### **Typical Characteristics**

Kinematic Viscosity, cSt @ 40°C	115.0
Kinematic Viscosity, cSt @ 100°C	15.20
Viscosity Index	138
TBN, mg KOH/g	9.5
Flash Point, COC, °C	210
Pour Point, oC, Max.	-30
CCS Viscosity @ -20 °C, cP, Max.	6700

Available configurations: 24 x 1L Case, 4 x 4L Case, 4 x 5L Case, 1 x 18L, 1 x 200L

This information only applies to products manufactured in the following location(s) – Singapore

Effective date  
28<sup>th</sup> April 2009

Authors Initials  
SKM

Product code