

---

---

# Product Information

A PRODUCT OF VALVOLINE INC. USA



---

## VALVOLINE ALL FLEET PLUS 30 & 40

**Valvoline All Fleet Plus 30 & 40** have been formulated from highly refined lube base stocks and carefully selected additive package comprising antioxidant, detergent/dispersant, antiwear and a special oil soot thickening control agent.

**Valvoline All Fleet Plus 30 & 40** are recommended for use in high speed naturally aspirated and turbo/super charged diesel engines of all makes operating at low speed and high torque conditions prevalent in prolonged city stop-&-go, on-&-off highway driving conditions including service in hilly regions.

---

### Performance levels / Approvals

---

API CF

---

### Typical Characteristics

---

| SAE Grade                        | 30    | 40    |
|----------------------------------|-------|-------|
| Kinematic Viscosity, cSt @ 40°C  | 95.62 | 139.6 |
| Kinematic Viscosity, cSt @ 100°C | 11.20 | 14.38 |
| Viscosity Index                  | 103   | 101   |
| TBN, mg KOH/g                    | 9.5   | 9.5   |
| Flash Point, COC, °C             | 210   | 220   |
| Pour point, °C                   | -36   | -30   |

---

Available configurations:

All Fleet Plus 30: 1 x 18L, 1 x 200L

All Fleet Plus 40: 24 X 1L Case, 4 x 5L Case, 1 x 18L, 1 x 200L

This information only applies to products manufactured in the following location(s) – Singapore

Effective date  
Oct 2016

Authors Initials  
AS