

PRODUCT INFORMATION



VALVOLINE™ 4T PREMIUM 20W-40

Premium 4T Oil for Motorcycles

Valvoline 4T Premium 20W-40 is a premium multi-grade 4T oil specially formulated to provide year-round protection for 4-Stroke motorcycle engines. The product is blended from selected base oil and additive chemistry to provide strong oil film for perfect protection and lubrication with reduced wear under a wide temperature range. It meets the requirements of leading motorcycle manufacturers.

Valvoline 4T Premium 20W-40 prevents clutch slippage and meets friction tests stipulated in JASO T903, 2016 Grade MA 2.

Valvoline 4T Premium 20W-40 is recommended for use in 4-Stroke models of all makes.

PERFORMANCE LEVEL
API SL
JASO MA2

Typical properties:

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

Typical Characteristics	
Kinematic Viscosity, cSt @ 40°C	127.50
Kinematic Viscosity, cSt @ 100°C	14.20
Viscosity Index	120
TBN, mg KOH/g (ASTM 2896)	7.3
Flash Point, COC, °C	230
CCS Viscosity @ -15 °C, cP, Max	7900

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales representative or through our website <https://sds.valvoline.com/>

This information only applies to products manufactured in the following location(s): Singapore

Effective date
AUG 2020

Author
AS