

PRODUCT INFORMATION



VALVOLINE ALL-FLEET PLUS 10W

Valvoline All-Fleet Plus 10W is blended from high refined mineral base stocks incorporating carefully selected detergent, dispersant and anti-oxidant additives to give the desired performance.

Valvoline All-Fleet Plus 10W is recommended for use in naturally aspirated and turbo-charged heavy duty diesel engines of heavy vehicles, earthmoving equipment operating under low ambient temperatures. The product is also recommended as hydraulic fluid type C2 specification of Detroit Diesel, Allison Division of General Motors, Komatsu and Caterpillar transmission systems.

PERFORMANCE LEVEL

API CF

Allison C-2

Typical properties:

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

Typical Characteristics	
Kinematic Viscosity, cSt @ 40°C	45.36
Kinematic Viscosity, cSt @ 100°C	7.16
Viscosity Index	131
TBN, mg KOH/g	7.4
Pour Point, °C,	-39
Flash Point, COC, °C	210
CCS Viscosity @ -25 °C, cP,	5100

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales representative or through our website <https://sds.valvoline.com/>

This information only applies to products manufactured in the following location(s): Singapore

Effective date
AUG 2020

Author
AS